


**SPACE LIGHT MODULATION ELEMENT AND IMAGE DISPLAY DEVICE**

**Publication number:** JP6235932  
**Publication date:** 1994-08-23  
**Inventor:** KURATOMI YASUNORI; OGAWA KUNI  
**Applicant:** MATSUSHITA ELECTRIC IND CO LTD  
**Classification:**  
**- International:** **G02F1/135; G02F1/13; (IPC1-7): G02F1/135**  
**- European:**  
**Application number:** JP19930020049 19930208  
**Priority number(s):** JP19930020049 19930208

Report a data error here

**Abstract of JP6235932**

**PURPOSE:**To attain high-contrast light modulation with a simple structure by fixing the light transmission section of a shielding means at the focal point of an image forming means having a variable focal distance. **CONSTITUTION:**A space light modulation element 1 is constituted of an image forming means 2 having a variable focal distance and a shielding means 4 provided with a light transmission section 3. The incidence light from a parallel light source 6 is fed to the image forming means 2. When the focal point of the image forming means 2 is changed to the first focal point 5, all the outgoing light 9 from the image forming means 2 passes through the light transmission section 3. When the focal point of the image forming means 2 is changed to the second focal point 8, most of the outgoing light 9' from the image forming means 2 is shielded by the shielding means 4, and only part of the light passing through the light transmission section 3 becomes the output of the space light modulation element 1. The output light quantity of the space light modulation element 1 can be changed when the focal point of the image forming means 2 is changed. If the focal point can be continuously changed from the first focal point 5 to the second focal point 8, the output light intensity of the space light modulation element 1 is continuously changed.



Data supplied from the esp@cenet database - Worldwide